

High Pressure Sodium Lamps

Description: HPST.250W/E40/HO

Performance Data


| | |
|---|------------------|
| Rated Light Output (Lumens @ 100 hours) | 33000 |
| Lamp Lumens per Watt | 132 |
| Rated Life (Hrs @ 10Hr./Start) | 32000 |
| Correlated Colour Temperature (K) | 2000 |
| Chromaticity (CIE - X Y) | 530,420 |
| Colour Rendering Index (CRI) or (Ra) | 25 |
| Typical Warm Up Time (Minutes) | 5 |
| Typical Hot Restart Time (Minutes) | 1 |
| Burning Position | Universal |
| Energy Rating (ErP) | A+ 275 kWh/1000h |

Physical Data


| | |
|----------------------------|---------------|
| Base Designation | E40 |
| Bulb Diameter (mm) | 46 |
| Max. Overall Length (mm) | 260 |
| Light Centre Length (mm) | 158 |
| Effective Arc Length (mm) | 64.3 |
| Max. Base Temperature (°C) | 250 |
| Max. Bulb Temperature (°C) | 400 |
| Luminaire Type | Open/Enclosed |
| Socket Pulse Rating (KV) | 5 |
| Mercury Content (mg) | 6.25 |

Lamp Electrical Data

| | |
|-------------------------------------|----------------|
| Nominal Lamp Wattage (W) | 250 |
| Lamp Operating Voltage (V) | 100 |
| Lamp Operating Current (A) | 3.0 |
| Min. Open Circuit Voltage (RMS) | 198 |
| Min. Starting Pulse (Peak V) | 2800-4500 |
| Min. Pulse Width (Microseconds) | 1 @2700V |
| Min. Pulse Rate Per ½ cycle | 1 |
| Pulse Position (Electrical Degrees) | 60-90, 240-270 |



Lumen Maintenance (Light Output vs. Rated Life)



Lamp Mortality (Survivors vs. Rated Life)

Revision: 01-06-2012

See page 2 for product notes

High Pressure Sodium Lamps

Notes:

This Product Specification contains data about typical performance at nominal power. Actual values may depend on ballast and applications. Complies with (CE), Low Voltage (CE), WEEE and RoHS Directives.